



Scapa 2721

PVC Lane Marking Adhesive Tape

DESCRIPTION

Scapa 2721 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubber-based adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability for use in lane marking and flooring applications

APPLICATIONS

- Colour coding
- Flooring and lane marking
- General splicing

PRODUCT BENEFITS

- Excellent resistance to abrasion, corrosion and moisture
- Suitable for indoor and protected outdoor environments
- Excellent conformability
- Easy transversal tearability
- Environmentally friendly technology
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)

TECHNICAL PROPERTIES

| | Unit | Value | Test Method |
|---------------------|------|-------|--------------|
| Nominal Thickness | mm | 0.16 | CEI EN 60454 |
| Tensile Strength | N/cm | 25 | CEI EN 60454 |
| Elongation at Break | % | 150 | CEI EN 60454 |
| Adhesion to Steel | N/cm | 1.5 | CEI EN 60454 |
| Adhesion to Backing | N/cm | 1.5 | CEI EN 60454 |

STANDARD PRESENTATION

- Roll length : 33 metres
- Roll width : 50, 75 and 100mm
- Core : 76mm Scapa branded cardboard core
- Packaging : Heat shrink sleeve
- Colours : Black, Yellow, White, Red, Blue, Light green

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Use within 24 months of receipt.

The tape should be applied with sufficient pressure to ensure an optimum bonding and prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.