



YÜZEY GELİŞTİRME MERKEZİ

TECHNICAL DATA SHEET

### 3954 PVC MASKING TAPE

<u>PRODUCT CODE</u>	: 3954
<u>PRODUCT</u>	: PVC Masking Tape
<u>BACKING</u>	: PVC
<u>COLOR</u>	: Orange
<u>TEMPERATURE RESISTANCE</u>	: 150 °C
<u>ADHESIVE SYSTEM</u>	: Natural Rubber
<u>ADHESION TO STEEL</u>	: 4,5 N / 25 mm
<u>THICKNESS</u>	: 0,12 mm
<u>TENSILE STRENGTH</u>	: 50 N / 25 mm
<u>ELONGATION AT BREAK</u>	: 80 %
<u>MAIN CHARACTERISTIC</u>	: High temperature resistant. This tape will perform in the presence of 150 C° temperatures for at least 1 hour and leave a sharp , clean separation line. Excellent adherence to wide variety of surfaces. Follows contours and remains in place as long as necessary. Leaves no residue upon removal.Meets the requirements of 2000/53/EC, ROHS 2002/95/EC and 2003/11/ EC directives.Product does not contain lead,mercury,cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE).
<u>SHELF LIFE &amp; STORAGE</u>	: Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

YGM self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each YGM product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that YGM self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.