



YÜZEY GELİŞTİRME MERKEZİ

TECHNICAL DATA SHEET

5408 TRANSFER TAPE

<u>PRODUCT CODE</u>	: 5408
<u>PRODUCT</u>	: Transfer Tape
<u>BACKING</u>	: No Backing
<u>LINER</u>	: Havana Brown Glassine
<u>TEMPERATURES RESISTANCE</u>	: - 40°C up to +140°C
<u>ADHESIVE SYSTEM</u>	: Solvent-Free Modified Acrylic
<u>ADHESION TO STEEL</u>	: 6,80 N / 25 mm
<u>THICKNESS</u>	: 0,08 mm
<u>MAIN CHARACTERISTIC</u>	: General purpose foam bonding e.g. gaskets, sound deadening and insulation materials. End uses involving critical temperature performance e.g. interior automotive trim, PU foams , felts , fabrics, fibres.
<u>SHELF LIFE & STORAGE</u>	: Shelf life of the product is 12 months after production. Rolls have to be stored vertically without direct sun contact and in room temperature of 20°C and humidity of 50%.

YGM self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each YGM product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that YGM self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.