



YÜZEY GELİŞTİRME MERKEZİ

TECHNICAL DATA SHEET

N-606 BONDING TAPE

CLOSED SIDE ADHESIVE TAPE

<u>BACKING</u>	: PET
<u>RELEASE LINER</u>	: HDPE Blue Release Liner
<u>ADHESIVE SYSTEM</u>	: Acrylic Solvent
<u>THICKNESS</u>	: 0,09 ± 0,01 MM
<u>ADHESION</u>	: 11,77 N (180° peel)
<u>TEST TEMPERATURE</u>	: 23 ± 2 C
<u>INITIAL TACK</u>	: < 10 cm

OPEN SIDE ADHESIVE TAPE

<u>PRODUCT</u>	: Transfer Tape
<u>BACKING</u>	: EVA Foam
<u>ADHESIVE SYSTEM</u>	: Solvent-free modified acrylic
<u>THICKNESS</u>	: 80 µ
<u>ADHESION STAINLESS STEEL</u>	: 1270 N / m 20 Min. (180° peel)
<u>SERVICE TEMPERATURE</u>	: 130 °C

EVA FOAM

<u>COLOUR</u>	: Black
<u>TEMPERATURE RESISTANCE</u>	: (- 20°C) - (100 °C)
<u>DENSITY</u>	: 70kg/m ³ (± 15kg /m ³)
<u>SHORE</u>	: 25-65 shore
<u>THICKNESS</u>	: 6 mm ± 0,3 mm
<u>TENSILE STRENGTH</u>	: 0,87 N/mm ²
<u>MAIN CHARACTERISTIC</u>	: Suitable for construction, decoration, white goods, automotive.

YGM self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each YGM product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that YGM self-adhesive tape which you envisage using is appropriate for your particular application. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.